



# Tiller

For skid-steer loaders



PALADIN LIGHT CONSTRUCTION

## FEATURES:

- available in 38", 52", & 68" working widths
- excellent landscape tool
- breaks up sod and clumps of soil
- mixes compost and other materials
- prepares soil for seeding or reseeding; great for small soil stabilization jobs
- dual direct drive motors propel both ends of the tiller drive shaft for balanced torque and minimal wear and tear
- hardened, replaceable tines cut to 6" deep



# Tiller

## FEATURES:

- no drive chains, no sprockets, and no extra gears
- more efficient use of hydraulics for lower system temperatures
- bi-directional shaft rotation permits under cutting and topcutting in both directions of travel
- offset tiller mounting permits work up close to walls, building and pipes, covers 76" wheel tracks
- 1 year warranty on structure  
6 month warranty on hydraulics

Specifications	38"	52"	68"
model number	LAF3438	LAF3452	LAF3468
weight (approximate)	435 lbs	600 lbs	695 lbs
working width	38"	52"	68"
overall width	44"	68"	78"
tines	20	28	36
GPM range	6 to 12	12 to 40	15 to 40
PSI range	1,500 to 3,000	2,000 to 3,500	2,300 to 3,500
torque @ 2,500 PSI	470 ft-lb	939 ft-lb	939 ft-lb
lift capacity	< 9,000 lbs		
operating weight	< 11,000 lbs		
Specifications and design are subject to change without notice and without liability, therefore, whenever applicable specifications are in accordance with SAE standards.			



PH: (800) 747-2132  
FX: (815) 824-2620

100 East Lee Road  
Lee, IL 60530  
United States of America

[www.paladinbrands.com](http://www.paladinbrands.com)



PALADIN LIGHT CONSTRUCTION  
F-Tiller Brochure 0702-1